



Liebert™ ITON

600VA - 2000VA



Best in class power protection and back up technologies for Offices and Home

The Liebert ITON Series is an economical line-interactive UPS that offers full-featured power protection for home or small office computers and electronic equipment. With it's unique features and extraordinary performance not normally found in similar products in range.



MODEL	SPECIFICATION	EXi 600 VA	LXi 600 VA	CX 600 VA	1000 VA LB
CAPACITY	VA/W	600 VA/360 Watt.	600 VA/360 Watt.	600 VA/360 Watt.	1000 VA/600 Watt.
INPUT	Voltage	220/230 VAC			
	Voltage Range	140-300 VAC			
	Frequency Range	50 Hz			
OUTPUT	AC Voltage Regulation (Batt. Mode)	±10%			
	Frequency Range (Batt. Mode)	50 Hz ±1 Hz			
	Transfer Time	Typical 2-6 ms			
	Waveform (Batt. Mode)	Simulated Sine Wave			
	Overload	110% +/-10% Shutdown after 5 mins			
BATTERY	Battery Type & Number	12 V/9Ah x 1	12 V/7 Ah x 2	12 V/7 Ah x 1	12VDC
	Floating Charge Voltage				13.7 VDC ± 2%
	Overcharge Protection				14.5VDC ± 2%
	Maximum Charge Current				20 A
	Typical Recharge Time	6-8 hours up to 90% capacity			
TRANSFER TIME	Minimum line break for transfer to battery	Typical 4-8 msec			
INDICATORS	AC Mode	Green lighting			
	Battery Mode	Green flashing			
	Fault	Red lighting			
ALARMS	"Battery Mode,Low Battery, Overload,Battery replacement,fault"	Audiable alarm is provided			
PROTECTION	Full Protection	Overload, discharge, and overcharge protection			
PHYSICAL	Dimension, D X W X H (mm)	282 x 101 x 142	353 X 150 x 162	279 X 101 X142	350 x 146 x 160
ENVIRONMENT	Net Weight (kgs)	4.7	7.8	4.2	9.0
	Operating Environment	0-40 Deg C.			
	Storage Temp	-15°C to 50°C			
	Humidity	0-95 % RH @ 0- 40°C (non-condensing)			
	Noise Level	Less than 40dB			

* Product specifications are subject to change without further notice

*Battery run time may vary depending upon load.

Liebert ITON Series

1000 VA - 2000 VA



Features and Benefits

- Smart RS232/USB interface for power management
- Excellent microprocessor control guarantees high reliability
- AVR boost and buck for voltage stabilisation
- Auto restart while AC is recovering
- Simulated sine wave
- Auto charging at Off-mode
- Cold start function
- Generator compatible



MODEL	SPECIFICATION	CX 1000 VA	CX 1500 VA	CX 2000 VA
CAPACITY	VA/W	1000 VA/600 Watt.	1500 VA/900 Watt.	2000 VA/1200 Watt.
INPUT	Voltage	220/230 VAC		
	Voltage Range	140-300 VAC		
	Frequency Range	50 Hz		
OUTPUT	AC Voltage Regulation (Batt. Mode)	±10%		
	Frequency Range (Batt. Mode)	50 Hz ±1 Hz		
	Transfer Time	Typical 2-6 ms		
	Waveform (Batt. Mode)	Simulated Sine Wave		
	Overload	110% +/-10% Shutdown after 5 mins		
BATTERY	Battery Type & Number	12 V/7 Ah x 2	12 V / 9 Ah x 2	12 V/ 9 Ah x 2
	Typical Recharge Time	6-8 hours up to 90% capacity		
TRANSFER TIME	Minimum line break for transfer to battery	Typical 4-8 msec		
INDICATORS	AC Mode	Green lighting		
	Battery Mode	Green flashing		
	Fault	Red lighting		
ALARMS	"Battery Mode,Low Battery, Overload,Battery replacement,fault"	Audiable alarm is provided		
PROTECTION	Full Protection	Overload, discharge, and overcharge protection		
PHYSICAL	Dimension, D X W X H (mm)	369 X 141 X 160	369 X 141 X 160	369 X 141 X 160
	Net Weight (kgs)	10	11.1	11.5
ENVIRONMENT	Operating Environment	0-40 Deg C.		
	Storage Temp	-15°C to 50°C		
	Humidity	0-95 % RH @ 0- 40°C (non-condensing)		
	Noise Level	Less than 40dB		

* Product specifications are subject to change without further notice

*Battery run time may vary depending upon load.



VertivCo.com | E-mail : marketing.india@vertivco.com | Toll free : 1-800-2096070

Vertiv Energy Private Limited | Plot C-20, Rd No.19, Wagle Ind Estate, Thane (W), 400604. India

© 2016 Vertiv Co. All rights reserved.